

# Retrieve Geo Details

This API lets you to retrieve the details of a specific Geo from PubMatic.



Before using PubMatic APIs, first generate your API Token to authenticate your API calls. For more information, see [Getting Started with PubMatic APIs](#).

## Request

URI	http://{domainName}/common/geo/{id}
HTTP Method	GET

## Request headers

Header Name	Type	Value	Required	Description
Authorization	String	Bearer \${access_token}	Yes	Need to send the access token generating for authentication at the place of \${access_token}. For more information about access tokens, see <a href="#">Getting Started with PubMatic APIs</a> .

## Request path parameters

Parameter Name	Type	Required	Description
id	integer	yes	ID of the geo.

### Example request call using CURL:

```
curl 'https://api.pubmatic.com/v1/common/geo/275439'
```

## Response

### Response headers

Response Header Name	Type
Content-type	application-json

### Response body

Response Body Parameter	Type	Description
geoid	Integer	Unique identifier for the geo.
name	String	Name of the geo.
countryCode	String	Country code for the geo.
dmaCode	Integer	DMA code for the geo.
geoLevel	String	Level of the geo. Possible values are CITY and COUNTRY.

### Sample response JSON

```
{
  "geoId": 5,
  "name": "Afghanistan",
  "countryCode": "AF",
  "dmaCode": 0,
  "geoLevel": "COUNTRY"
}
```

## Error codes

Error codes specific to this API method.

Error Code	Error Description
CC03_004	Resource not found